



FOSFAMIX

Phosphatising agent



An iron phosphating agent for spray processes and grease removal from aluminium and zinc surfaces. Forms an even phosphate layer up to 1.4 g/m² thick, improving paint adhesion.

Application	For iron phosphating of steel prior to painting in spray processes. Also suitable for the grease removal washing of aluminium and zinc-coated materials.		
Product properties	Fosfamix forms an even layer of phosphate up to 1.4 g/m ² thick on ferrous metals, improving paint adhesion and acting as an anti-corrosion layer.		
Instructions for use	Dosage:	1 - 2 %	
	Treatment time:	1-3 minutes	
	Operation temperature:	40 -70 °C	
	Use solution pH:	3,5 - 5,5	
Note	The Fosfamix bath has a very strong oil-separation capacity. We recommend to use an oil-separator on a regular basis.		
Composition	Ingredient		
	Sodium phosphate	15 - 30 %	
	Phosphoric acid	5 - 15 %	
	Anionic surfactants	< 5 %	
	Non-ionic surfactants	< 5 %	
Country of manufacture	FINLAND		
Package size / Product code	Sales unit	Product Code	GTIN
	1 x 20 l	423465	6417964481273
	1 x 200 l	423469	6417964481280
Additional information	Check the updated version of a paper brochure on our website at www.kiilto.com/en or send an e-mail to our customer service at asiakaspalvelu@kiilto.com .		